

RUROCIĄG POJEDYŃCZY C.O. 95°C 6 bar, c.w. 70°C 10 bar


Obudowa zewn. m/m	235	200	160	160	140	125	110	110	110
Rura PE-X zewn. m/m	125	110	90	75	63	50	40	32	25
Średnica wewn. m/m	102,2	90	73,6	61,2	51,4	40,8	32,6	26	20
Promień zginania mb	1,35	1,20	1,10	0,80	0,55	0,45	0,35	0,25	0,25
Nr katalogowy	1.001	001	002	003	004	005	006	007	008

**RUROCIĄG PODWÓJNY C.O. 95°C 6 bar**


Obudowa zewn. m/m	235	200	200	160	160
Rura PE-X zewn. m/m	2 x 63	2 x 50	2 x 40	2 x 32	2 x 25
Średnica wewn. m/m	2 x 51,4	2 x 40,8	2 x 32,6	2 x 26	2 x 20,4
Promień zginania mb	1,10	0,80	0,60	0,50	0,50
Nr katalogowy	009	010	011	012	013

**RUROCIĄG PODWÓJNY C.W. 70°C 10 bar**

Obudowa zewn. m/m	293	235	200	200	200	160	160
Rura PE-X zewn. m/m	1 x 90 1 x 50	1 x 75 1 x 40	1 x 63 1 x 32	1x50 1x32	1 x 50 1 x 25	1 x 40 1 x 25	1 x 32 1 x 20
Średnica wewn. m/m	1 x 73,6 1 x 40,8	1 x 61,2 1 x 32,6	1 x 51,4 1 x 26	1x40,8 1x26	1 x 40,8 1 x 20,4	1 x 32,6 1 x 20,4	1 x 26 1 x 16
Promień zginania mb	1,20	0,90	0,80	0,80	0,80	0,60	0,50
Nr katalogowy	014	015	016	017.1	017	018	019

**RUROCIĄG POCZWÓRNY - C.O. 95°C 6 bar, C.W. 70°C 10 bar**

Obudowa zewn. m/m	293	235	235	235
Rura PE-X zewn. m/m	2 x 75 1 x 50 1 x 32	2 x 63 1 x 40 1 x 32	2 x 50 1 x 50 1 x 32	2 x 50 1 x 40 1 x 25
Średnica wewn. m/m	2 x 61,2 1 x 40,8 1 x 26	2 x 51,4 1 x 32,6 1 x 20,4	2 x 40,8 1 x 40,8 1 x 26	2 x 40,8 1 x 32,6 1 x 20,4
Promień zginania mb	1,20	1,20	1,00	1,00
Nr katalogowy	020	020-1	021	021-2

**RUROCIĄG POCZWÓRNY - C.O. 95°C 6 bar, C.W. 70°C 10 bar**

Obudowa zewn. m/m	200	200	200	160
Rura PE-X zewn. m/m	2 x 50 1 x 32 1 x 20	2 x 40 1 x 32 1 x 20	2 x 32 1 x 25 1 x 20	2 x 25 1 x 20 1 x 16
Średnica wewn. m/m	2 x 40,8 1 x 26 1 x 16	2 x 32,6 1 x 26 1 x 16	2 x 26 1 x 20,4 1 x 16	2 x 20,4 1 x 16 1 x 12
Promień zginania mb	0,90	0,70	0,60	0,60

